



Wet saws



Ideal for cutting ceramics, porcelain, reinforced grès and other materials — up to 6 cm in a single pass.

Available in 3 standard lengths, or built-to-order in custom length.

- 2 HP engine, direct-on-disc
- 100% Aluminium table chassis and covers
- Stainless steel head rails and adjustable armoured ball bearings
- Polyethylene water basin with screw-in cap
- Water cooling system featuring armoured pipe, metallic tap and bilateral blade spray terminals
- Magnetic-induction pump
- PVC cable/pipe protection chain
- Cutting head's vertical tilt system allows for cut depth adjusting
- Cutting system's side tilt capability eases up to 45° ("mitre") cut
- Front, back and bilateral side blade protection devices included
- Electrical system featuring magneto thermal protection and release coil
- Retractable legs include fall-protection device
- Table handles and transport wheels included
- Supports \varnothing 250 and \varnothing 300 blades



ART	⚡	KW	Hp	RFM	mm	cm	cm	cm	cm	mm cut	mm cut	mm cut	Kg	⊕	cm.
SqualoMAX	1141	230V	1,5	2	2800	250 300	61 60	73 60	42x42 42x42	4,5 6	6 6	52	1	120x65xh80	
SqualoMAX 100	1142	230V	1,5	2	2800	250 300	91 90	103 90	64x64 64x64	4,5 6	6 6	55	1	150x65xh80	
SqualoMAX 130	1143	230V	1,5	2	2800	250 300	121 120	133 120	84x84 84x84	4,5 6	6 6	58	1	180x65xh80	

ITALIAN MANUFACTURER

Machinery and tools for professional tilers and bricklayers