

SQUALO





Ideal for cutting ceramics, porcelain, reinforced grès and other materials — up to 5 cm in a single pass.

Available in 3 standard lengths, or built-to-order in custom length.

- 1.5 HP engine, direct-on-disc
- 100% Aluminium table chassis and covers
- Stainless steel head rails and adjustable armoured ball bearings
- Polyethylene water basin with screw-in cap
 Water and live and the fact with screw-in cap
- Water cooling system featuring armoured pipe, metallic tap and bilateral blade spray terminals
- Magnetic-induction pump
- PVC cable/pipe protection chain
- Cutting head's vertical tilt system allows for cut depth adjusting
- Cutting system's side tilt capability eases up to 45° ("mitre") cut
- Front, back and bilateral side blade protection devices included
- Electrical system featuring magneto thermal protection and release coil
- Retractable legs include fall-protection device
- Table handles and transport wheels included
- Supports \varnothing 180 and \varnothing 200 blades



		ART	•	kW	Нр	(RPM)	© _{mm}	©	om			Double Cut off	Kg	(i cm.
	Squalo	1132	230V	1,1	1,5	2800	180	61	73		4		50	1	120x60xh80
	- 4						200	60	75	42x42	5	5,5			
	Squalo 100	1133	230V	1,1	1,5	2800	180	91 90	103 105	64x64 64x64	4 5	5,5 5,5	53	1	150x55xh80
(E)	Squalo 130	1134	230V	1,1	1,5	2800	180	121	133	84x84	4	5,5	56 1	1	180x55xh80
							200	120	135	84x84	5	5,5		ı	

ITALIAN MANUFACTURER

Machinery and tools for professional tilers and bricklayers