

SQUALO TOP







Available in 3 standard lengths, or built-to-order in custom length.

- 3 HP engine, direct-on-disc
- 100% Aluminium table chassis and covers
- Stainless steel head rails and adjustable armoured ball bearings
- Polyethylene water basin with screw-in cap
 Water goding system feeturing armoured.
- Water cooling system featuring armoured pipe, metallic tap and bilateral blade spray terminals
- Magnetic-induction pump
- PVC cable/pipe protection chain
- Cutting head's vertical tilt system allows for cut depth adjusting
- Cutting system's side tilt capability eases up to 45° ("mitre") cut
- Front, back and bilateral side blade protection devices included
- Electrical system featuring magneto thermal protection and release coil
- Retractable legs include fall-protection device
- Table handles and transport wheels included
- Supports \varnothing 250 and \varnothing 300 blades



		ART	•	kW	Нр	(RPM)	© _{mm}	om	© om	Com Com		Double Cut off	Kg	(6)	↓ Com.
	SqualoTOP	1112	230V	2,2	3	2800	250 300	61 60	73 75	42x42 42x42	4.5 6	6	53	1	120x60xh80
	SqualoTOP 100	1113	230V	2,2	3	2800	250 300	91 90	103 105	64x64 64x64	4.5 6	6	56	1	150x55xh80
(E	SqualoTOP 130	1114	230V	2,2	3	2800	250 300	121 120	133 135	84x84 84x84	4.5 6	6	59	1	180x55xh80

ITALIAN MANUFACTURER

Machinery and tools for professional tilers and bricklayers